**Monitoring Requirements** 

Monitoring Requirements		1
LSM Permit	UIC Class III	NRC License
Operational Groundwater		
Monitoring Domestic Wells		
Duration: from the onset of ISR		
operations until groundwater		
restoration is approved by NRC		
Range: domestic wells within 2		
km of the perimeter monitor		
well rings.		
Frequency: Samples will be		
collected annually		
Analyzed for the constituents		
listed in Table 6.2-1.		
Operational Groundwater		
Monitoring Stock Wells		
Duration: only During operation		
Range: all stock wells within the	Ex. 5 Deliberative Process (DP)	
permit area. Frequency: Samples	LA. J Deliberative Flucess (DF)	
will be collected quarterly		
Analyzed for water level and the		
three excursion indicators of		
chloride, total alkalinity, and		
conductivity.		
Operational Groundwater		
Monitoring		
Monitor Wells		
Duration: from the onset of ISR		
operations through NRC		
approval of groundwater		
restoration		
A list of the monitor wells		
included in the operational		
monitoring program is provided		
in Table 5.5-1. Monitor wells		
included in the operational		
monitoring program are		
depicted on Figures 5.5-1		
through 5.5-6 and include		
domestic wells, stock wells, and wells completed in the alluvium,		
Fall River, Chilson, and Unkpapa.		
Monitored quarterly		
Analyzed for constituents listed		
in Table 6.2-1		
III TADIC U.Z-I		

